

V Series™ HD

Bridgelux Differentiation

- 10+ years of driving LED industry transformation
- Global strategic partnerships
- Accredited ENERGY STAR® and application labs
- Broadest portfolio of color points



Features

- Ultra-high lumen density & center beam candle power
- Available in variety of color points including Décor Series™ Class A (CRI 93) and Décor Series™ Ultra (CRI 97)
- Significantly reduced thermal resistance
- Industry leading color over angle uniformity

Benefits

- Enables compact fixture design, lowers operating costs
- Reliable use at elevated currents enables greater design flexibility
- High quality, true color reproduction
- 2x the lifetime of ceramic metal halides



Applications

- Retail & Hospitality
- Architectural & Museums
- Industrial & Warehouse
- Residential



Product	CCT Range	CRI	SDCM	Typ. Flux (lm)* 3000K, 80CRI	Drive Current (mA)	Voltage*	Efficacy (lm/W)* 3000K, 80CRI	LES (mm)
V4 HD	2700K-4000K	80, 90, 93, 97	3	765	175	36.4	120	4
V6 HD	2700K-4000K	80, 90, 93, 97	3	1587	350	36.4	125	6
V9 HD	2700K-4000K	80, 90, 93, 97	3	3417	700	36.4	134	9

* All measurements are at T_c = 25°C