



Access Solutions

HVAC SOLUTIONS



TEL. +90 212 721 4444
info@mesanlocks.com

MESAN KİLİT A.Ş.
Alipasa Sanayi Bölgesi,
Ulugbey Sokak No: 7
34570 Silivri İstanbul Türkiye
Fax. +90 212 721 4445

www.mesanlocks.com

MAKING IT EASIER

LOCKS / LATCHES



NEW HVAC LOCK

- Ergonomic and stylish design
- Quick fixing
- Secure locking
- Adjustable grip length
- Suitable for outward swing doors



HVAC LOCK

- Nylon body with steel cam
- Can be used for left or right hand doors
- Roller cam allows locking using low force
- Removable handle allows easy on-site fitting
- Available with Eurokey (5333) or no lock
- Internal handle enables safe opening from the inside



FUNCTIONAL LOCKING HINGE

- Lock can also be used as hinge
- Door can be completely removed by unlocking the both products



HVAC LOCK OUTSIDE LOCKING

- Outside locking system provides safety for pressurised doors
- For logo application please contact Essentra



ADJUSTABLE COMPRESSION LATCHES

- Chrome Plated or Black Powder Coated Die-Cast Zinc
- 6mm Compression
- Cam can be used forward or reversed
- Latch provides good compression and noise isolation



STEPPED COVER LOCK

- For soundproof or isolated doors
- Tight closure achievable with 270° cam rotation and stepped cam



QUARTER TURN LOCK - SPRING LOADED

- Suitable for use on thick panels such as insulated panels
- 5mm Double Bit Head
- Seals to IP65
- Supplied with rubber sealing gasket



OUTSIDE LOCKING HANDLE

- Outside locking system provides safety for the pressurized door



ACCESSORIES

CIRCULAR INSPECTION WINDOW

- Visual inspection of HVAC enclosures
- Adjustable for 30-60 mm isolated doors



CLAMPS (3D)

- Available in all die-cast zinc alloy
- 3D capability
- High mechanical resistance



EMERGENCY STOP BUTTON

- Easy to install
- Different contact options (max. 3 contact)
- Standard wire length is 2.5 m
- Standard conduit length is 2 m



BRIDGE CLAMPS

- Nylon with Steel screw
- Ideal for heating and ventilation panels
- Suitable for right or left hand doors



HINGES



3D ADJUSTABLE HVAC HINGE

- Allows three dimensional adjustments
- Height ± 2mm, Width ± 2mm, Depth ± 2mm
- Ideal for large flush fitting doors
- Suitable for air conditioning, electrical panels and machinery covers
- Stainless steel pin



HVAC HINGE

- Specially designed for air conditioning central units
- Also used for plain/flush mounted heavy doors
- Hinge rotation angle 180°



3D ADJUSTABLE HVAC HINGE

- Hinge supplied pre-assembled to decrease labour costs
- Two-dimensional door adjustment possible
- Axial adjustment is ± 2 mm. Radial adjustment is ± 1 mm.



HVAC HINGE

- Specially designed for central air conditioning units
- Stylish design
- Supplied with polyamide hinge cover and Stainless steel (AISI 304) hinge pin

HANDLES / GASKETS

PULL HANDLE

- Deep grip handle
- Carrying capacity 750N / Pair
- Compact and Ergonomic design
- Installed by pushing handle into mounting hole



COVER HANDLE

- Available for fixing with either hex bolts or cross-head screws.



TOP BUBBLE GASKET

- Supplied in rolls of 20m
- Clip on profile offering edge protection and sealing
- Profiles are flexible and are pressed on by hand
- With steel spring core



EPDM SPONGE ADHESIVE SEAL

- Supplied in rolls of 10m
- Easy to apply adhesive seal
- Ideal for metal enclosures

