

								*	*	*	*	
Cardinal	Pkg		Pkg		Surface	Freq	Operating	Stability	Tolerance	Load	Series	factory
Series	Type				Area	Range	Temperature	Std	Std.	Capacitance	Resistance	lead-time
		L	W	H		MHz	Range T _{opr}			C _L pF	R1	weeks
		mm	mm	mm	Sq mm	f *	A1,A2,A3 **	Other options available	Other options available	Other options available	Other options available	
Through Hole												
C49	Metal	11.1	4.7	13.6	52	3.5 - 200	A1,A2,A3	50ppm	50ppm	18	See Web Site for options	4 to 6
C49J	Metal	17.6	11.1	5.3	195	3.5 - 200	A1,A2,A3	50ppm	50ppm	18	See Web Site for options	4 to 6
CLP	Metal	11.1	4.7	3	52	3.5 - 75	A1	50ppm	50ppm	18	See Web Site for options	4 to 6
CM1	Metal	7.8	3.2	8.1	25	7 - 175	A1,A2,A3	50ppm	50ppm	18	See Web Site for options	5 to 7
CM1J	Metal	7.8	3.2	12.5	25	7 - 175	A1,A2,A3	50ppm	50ppm	18	See Web Site for options	5 to 7
CMS8	Metal		3	8.9		3.5 - 64	A1	50ppm	50ppm	18	See Web Site for options	5 to 7
CTF6	Metal		2	6		30 - 200 KHz	A1	-(.035)ppm/ (0C-250C)2	30ppm	12.5	50 K Ohm	5 to 7
CTF8	Metal		3	8.9		30 - 200 KHz	A1	-(.035)ppm/ (0C-250C)2	30ppm	12.5	50 K Ohm	5 to 7
						32.768 std	A1					
Surface Mount												
CSM1	Metal	11.4	4.7	4.3	54	3.5 - 75	A1,A2	50ppm	50ppm	18	See Web Site for options	4 to 6
CSM4	Metal	11.4	4.7	3.2	54	3.5 - 75	A1,A2	50ppm	50ppm	18	See Web Site for options	4 to 6
CSM5	Metal	11.4	4.7	2.5	54	3.5 - 75	A1,A2	50ppm	50ppm	18	See Web Site for options	4 to 6
CX17A	Ceramic	7.5	5.1	1.7	38	10 - 100	A1,A2	100ppm	50ppm	16	See Web Site for options	6 to 7
CX051	Metal	7.5	5.1	1.3	38	9.8 - 100	A1,A2	50ppm	50ppm	16	See Web Site for options	6 to 7
CX5	Metal	7.2	5.2	1.2	37	9 - 150	A1,A2	50ppm	50ppm	Parallel	See Web Site for options	6 to 7
CX406	Metal	12.5	4.85	4	61	3.5-75	A1,A2	50ppm	50ppm	18	See Web Site for options	6 to 7
CX505	Metal	12.5	4.85	5	61	3.5-75	A1,A2	50ppm	50ppm	18	See Web Site for options	6 to 7
CX506	Metal	12.5	4.85	5	61	3.5-75	A1,A2	50ppm	50ppm	18	See Web Site for options	6 to 7
CX47	Ceramic	7.2	5.2	1.3	37	14 - 60	A1,A2	50ppm	50ppm	Parallel	See Web Site for options	6 to 8
CX635A	Ceramic	6	3.5	1.1	21	11-150	A1,A2	50ppm	50ppm	18	See Web Site for options	8 to 10
CX325	Ceramic	3.2	2.5	0.8	8	20 - 40	A1	50ppm	50ppm	16	See Web Site for options	14 to 16
CPFB	Plastic	8.7	3.7	2.5	32	32.768 KHz	A1,A2	-(.035)ppm/ (0C-250C)2	20ppm	12.5	50 K Ohm	6 to 8
CPTB	Plastic	10.4	4.2	3.4	44	32.768 KHz	A1,A2	-(.035)ppm/ (0C-250C)2	20ppm	12.5	50 K Ohm	6 to 8
CT5	Plastic	8.9	2.4	2	21	32.768 - 76.800 KHz	A1	-(.035)ppm/ (0C-250C)2	50ppm	6 or 12.5 pF	50 K Ohm	8 to 10

** A1= -10⁰C to + 70⁰C
 A2= -40⁰C to + 85⁰C
 A3= -55⁰C to 125⁰C

* Other selections available
 This information is for guidance purposes only--Cardinal produces full custom products to your specification.